

Description

Insert part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1836C0809M
Minimum Qty (MOQ):	10 EA
NSN:	5325-01-158-9956
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1836C08-09M Specifications

Flange Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Flange Thickness:	0.060 Inches Nominal
Length:	0.281 Inches Nominal
Insert Size:	0.260 In. Dia
Full Internal Thread Length:	0.187 Inches Nominal
Features Provided:	Individually Keyed
Special Features:	Solid Film Lubricant,mil-I-8937 Inside Of Insert Only
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1836 Professional/industrial Association Standard

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C08-09M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.