

**Description**

length: 0.343", thread: 8-32, blind threaded, lightweight, corrosion resistant steel, NAS1836 series insert

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1836C0811
Minimum Qty (MOQ):	10
NSN:	5325-01-340-1288
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N NAS1836C08-11 Specifications

<b>Flange Diameter:</b>	0.441 Inches Minimum And 0.451 Inches Maximum
<b>Overall Length:</b>	0.341 Inches Nominal
<b>Hole Type:</b>	Threaded
<b>Flange Thickness:</b>	0.060 Inches Nominal
<b>Insert Style:</b>	Protruding Flange
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Size And Series/type Designator:</b>	0.1640-32 Unjc
<b>Specification/standard Data:</b>	80205-nas1836 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C08-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.