

Description

length: 0.343", thread: 8-32, blind threaded, lightweight, corrosion resistant steel, NAS1836 series insert

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1836C0811 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-01-340-1288 |
| Schedule B: | 7318.16.0060 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N NAS1836C08-11 Specifications

| | |
|---|--|
| Flange Diameter: | 0.441 Inches Minimum And 0.451 Inches Maximum |
| Overall Length: | 0.341 Inches Nominal |
| Hole Type: | Threaded |
| Flange Thickness: | 0.060 Inches Nominal |
| Insert Style: | Protruding Flange |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Size And Series/type Designator: | 0.1640-32 Unjc |
| Specification/standard Data: | 80205-nas1836 Professional/industrial Association Standard |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C08-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.