

**Description**

length: 0.219", thread: 10-32, blind threaded sandwich panel, lightweight, corrosion resistant steel, NAS1836 series insert

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1836C307
Minimum Qty (MOQ):	20
NSN:	5325-01-628-6178
Schedule B:	7318.16.0060
ECCN:	EAR99



## P/N NAS1836C3-07 Specifications

<b>Flange Diameter:</b>	0.441 Inches Minimum And 0.451 Inches Maximum
<b>Overall Length:</b>	0.217 Inches Nominal
<b>Sleeve Diameter:</b>	0.260 Inches Nominal
<b>Hole Type:</b>	Threaded
<b>Flange Thickness:</b>	0.60 Inches Nominal
<b>Insert Style:</b>	Protruding Flange
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm-a582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Size And Series/type Designator:</b>	0.190-32 Unjf
<b>Specification/standard Data:</b>	80205-nas1836 Professional/industrial Association Standard

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C3-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.