

Description

length: 0.375", thread: 10-32, blind threaded sandwich panel, lightweight, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1836C312
Minimum Qty (MOQ):	20
NSN:	5325-01-357-7436
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N NAS1836C3-12 Specifications

Flange Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Sleeve Diameter:	0.260 Inches Nominal
Hole Type:	Threaded
Flange Thickness:	0.060 Inches Nominal
Insert Style:	Protruding Flange
Special Features:	Pin Overall Length Is 0.375 Inch Nominal
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Size And Series/type Designator:	0.190-32 Unjf
Specification/standard Data:	80205-nas1836 Professional/industrial Association Standard

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.