

Description

Thread Size: 3/16", Head Width: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1836C318 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5325-00-038-8595 |
| Schedule B: | 7318.16.0060 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N NAS1836C3-18 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Flange Diameter: | 0.430 Inches Maximum |
| Flange Thickness: | 0.060 Inches Nominal |
| Length: | 0.550 Inches Nominal |
| Second Flange Thickness: | 0.030 Inches Minimum |
| Width Across Flats: | 0.441 Inches Minimum And 0.451 Inches Maximum |
| Insert Size: | 0.250 In. Dia |
| Features Provided: | Individually Keyed |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flange |
| Thread Series Designator: | Unjf |

How to Order

Order this insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1836C3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.