

Description

Thread Size: 1/4", Length: 1-", Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1860CA13
Minimum Qty (MOQ):	1 EA
NSN:	5307-01-332-1526
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1860CA13 Specifications

Thread Class:	3a Nut Thread
Thread Class:	3a Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.255 Inches Minimum Stud Thread And 0.295 Inches Maximum Stud Thread
Thread Length:	0.427 Inches Minimum Nut Thread And 0.447 Inches Maximum Nut Thread
Locking Feature:	Ring, Lock Keyed
Overall Length:	1.124 Inches Nominal
Thread Quantity Per Inch:	28 Stud Thread
Thread Quantity Per Inch:	32 Nut Thread
Nominal Thread Size:	0.190 Inches Nut Thread
Nominal Thread Size:	0.250 Inches Stud Thread
Distance From End Of Stud End Threads To Nut End:	0.813 Inches Nominal
Special Features:	160000 Psi Min. Tensile Strength
Material:	Steel Comp 410 Or Steel Comp 420 And Iron Alloy 660
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Locked In
Thread Series Designator:	Unjf Nut Thread
Thread Series Designator:	Unjf Stud Thread
Specification/standard Data:	80205-nas1860 Professional/Industrial Association Standard

How to Order

Order this stud assembly from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1860CA13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.