

## P/N NAS1870-3-2

### **Description**

height 0.312", thread: 10-32, two lug floating nutplate, deep counter bore

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS187032

Minimum Qty (MOQ): 25

NSN: 5310-00-826-6131

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1870-3-2 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Mounting Hole Diameter:	0.980 Inches Minimum And 0.985 Inches Maximum
Nut Style:	Plate
Nut Length:	0.940 Inches Maximum
Nut Height:	0.125 Inches Minimum And 0.272 Inches Maximum
Plate Thickness:	0.020 Inches Minimum And 0.030 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1870-3-2</a> and selecting the