

P/N NAS1870-3-5K

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS187035K

Minimum Qty (MOQ): 15 EA

NSN: 5310-01-252-7283

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1870-3-5K Specifications

3b
Right-hand
Prevailing Torque All Metal Design
0.194 Inches Minimum Nut
Dry Film Lubricant
0.098 Inches Minimum And 0.103 Inches Maximum
Plate
0.948 Inches Maximum
0.500 Inches Maximum
0.032 Inches Maximum
0.416 Inches Maximum
0.312 Inches Minimum Nut
Countersunk Holes Or Dimpled Holes
Opposite Nut Projection Side
2 Holes
0.339 Inches Minimum And 0.349 Inches Maximum
0.686 Inches Minimum And 0.690 Inches Maximum
450.0 Deg Fahrenheit Nominal
Unjf
Floating Nut
32
49.0 Rockwell C Maximum
0.190 Inches
98.0 Degrees Minimum And 102.0 Degrees Maximum
Steel Overall
Cadmium Overall
Qq-p-416 Fed Spec Single Treatment Response Overall
80205-nas1870 Professional/industrial Association Standard

How to Order

