

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS187035K
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-252-7283
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1870-3-5K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.500 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Counterbore Depth:	0.312 Inches Minimum Nut
Nut Mounting Provision:	Countersunk Holes Or Dimpled Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1870 Professional/Industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1870-3-5K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.