



Military-Fasteners.com

P/N NAS1870CL3-6

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1870CL36
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-133-1588
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1870CL3-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Base
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.562 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Counterbore Depth:	0.375 Inches Minimum Base
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.688 Inches Nominal
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1870 Professional/Industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1870CL3-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.