

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919B0401FC
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-185-9961
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1919B04-01FC Specifications

Fastener Length:	0.198 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Shear Strength:	495 Single Pounds Per Square Inch
Special Features:	Self-locking
Material:	Aluminum Alloy 5056 Sleeve Or Aluminum Alloy 2024 Sleeve
Material:	Aluminum Alloy 5056 Stem Or Aluminum Alloy 2024 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve Or Mil-a-8625 Mil Spec 1st Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem Or Mil-a-8625 Mil Spec 1st Treatment Response Stem
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04-01FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.