

**Description**

size: 1/8", grip range: 1/8" - 3/16", protruding head general purpose, aluminum, NAS1919 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1919B0403        |
| Minimum Qty (MOQ):      | 10                  |
| NSN:                    | 5320-00-151-5520    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N NAS1919B04-03 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.323 Inches Maximum                                       |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum              |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.128 Inches Maximum              |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                     |
| <b>Head Major Diameter:</b>                           | 0.238 Inches Minimum And 0.262 Inches Maximum              |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                       |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum              |
| <b>Shear Strength:</b>                                | 495 Single Pounds Per Square Inch                          |
| <b>Special Features:</b>                              | Self-locking   |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Stem                                   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                                 |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve          |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem            |
| <b>Surface Treatment:</b>                             | Chromate Stem  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve          |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec 1st Treatment Response Stem            |
| <b>Specification/standard Data:</b>                   | 80205-nas1919 Professional/Industrial Association Standard |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.