



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1919B04-04**

## Description

size: 1/8", grip range: 3/16" - 1/4", protruding head general purpose, aluminum, NAS1919 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1919B0404
Minimum Qty (MOQ):	10
NSN:	5320-00-176-6281
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

# P/N NAS1919B04-04 Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Universal
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	495 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5056 Sleeve Or Aluminum Alloy 2024 Sleeve
Material:	Aluminum Alloy 5056 Stem Or Aluminum Alloy 2024 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Sleeve Or Anodize Sleeve
Surface Treatment:	Chromate Stem Or Anodize Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Stem Or Mil-a-8625 Mil Spec 2nd Treatment Response Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Sleeve Or Mil-a-8625 Mil Spec 2nd Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.