

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919B0407
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-607-8102
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1919B04-07 Specifications

Fastener Length:	0.573 Inches Maximum
Head Style:	Universal
Head Height:	0.54 Inches Nominal
Shank Diameter:	0.1240 Inches Minimum And 0.1285 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	B-2 Bomber
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet,blind-general Purpose,bulbed,protruding Head,mechanically-locked-spindle
Material:	Aluminum Alloy 2024 Grip
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 National Std/spec Single Material Response Grip
Material Document And Classification:	Qq-a-430 National Std/spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 National Std/spec Single Material Response Sleeve
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.