

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B04S01
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-232-3942
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1919B04S01 Specifications

Fastener Length:	0.198 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Special Features:	Self Locking
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment:	Anodize Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.