

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1919B04S01                             |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5320-01-232-3942                          |
| Schedule B:             | 7616.10.3000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE  
AVAILABLE

## P/N NAS1919B04S01 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.198 Inches Nominal  |
| <b>Head Style:</b>                                    | Universal   |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.128 Inches Maximum   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                           | 0.238 Inches Minimum And 0.262 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.025 Inches Minimum And 0.062 Inches Maximum   |
| <b>Special Features:</b>                              | Self Locking  |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Stem  |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem   |
| <b>Surface Treatment:</b>                             | Anodize Sleeve  |
| <b>Surface Treatment:</b>                             | Anodize Stem  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Sleeve |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Stem   |
| <b>Specification/standard Data:</b>                   | 80205-nas1919 Professional/industrial Association Standard  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.