

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B04S01
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-232-3942
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1919B04S01 Specifications

<b>Fastener Length:</b>	0.198 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.025 Inches Minimum And 0.062 Inches Maximum
<b>Special Features:</b>	Self Locking
<b>Material:</b>	Aluminum Alloy 2024 Stem
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Sleeve
<b>Surface Treatment:</b>	Anodize Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Or Mil-c-5541 Mil Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas1919 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.