

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1919B04S02 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5320-01-101-5596 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N NAS1919B04S02 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.260 Inches Nominal |
| Head Style: | Brazier |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Aluminum Alloy 2024 Expander |
| Material: | Aluminum Alloy 5056 Sleeve |
| Surface Treatment: | Anodize Expander |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.