

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B04S02
Minimum Qty (MOQ):	25
NSN:	5320-01-101-5596
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N NAS1919B04S02 Specifications

Fastener Length:	0.260 Inches Nominal
Head Style:	Brazier
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Aluminum Alloy 2024 Expander
Material:	Aluminum Alloy 5056 Sleeve
Surface Treatment:	Anodize Expander

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.