

Description



Fastener Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1919B04S03 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-087-6118 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N NAS1919B04S03 Specifications

| | |
|---|--|
| Fastener Length: | 0.323 Inches Nominal |
| Head Style: | Undercut Pan No. 2 |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Material: | Aluminum Alloy 2024 Stem |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Locking Ring |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Anodize Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1919 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.