

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B04S05
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-180-5130
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1919B04S05 Specifications

Fastener Length:	0.448 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Surface Treatment:	Anodize Stem
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B04S05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.