

**Description**

Fastener Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1919B05S02
Minimum Qty (MOQ):	25
NSN:	5320-01-097-5469
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1919B05S02 Specifications

<b>Fastener Length:</b>	0.263 Inches Nominal
<b>Head Style:</b>	Brazier
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Minimum Tensile Strength:</b>	490 Pounds Per Square Inch
<b>Shear Strength:</b>	755 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2024 Expander
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Surface Treatment:</b>	Anodize Expander

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.