

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B05S02
Minimum Qty (MOQ):	25
NSN:	5320-01-097-5469
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1919B05S02 Specifications

Fastener Length:	0.263 Inches Nominal
Head Style:	Brazier
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.312 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Minimum Tensile Strength:	490 Pounds Per Square Inch
Shear Strength:	755 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2024 Expander
Material:	Aluminum Alloy 5056 Sleeve
Surface Treatment:	Anodize Expander

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.