

Description

Fastener Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919B05S02FC
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-490-6644
Schedule B:	7616.10.3000
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1919B05S02FC Specifications

Fastener Length:	0.478 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Knob Stem-type K
End Item Identification:	F-22
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Special Features:	For Use With Single Action Hand Held Installation Tools Or Automatic Installation Equip. Marked With A Depressed "s" On Spindle Head Or Coded Yellow On Spindle
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S02FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.