

**Description**

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B05S03FC
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-491-5012
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N NAS1919B05S03FC Specifications

<b>Fastener Length:</b>	0.350 Inches Maximum
<b>Head Style:</b>	Modified Pan
<b>Head Height:</b>	0.067 Inches Minimum And 0.155 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S03FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.