

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B05S04
Minimum Qty (MOQ):	20
NSN:	5320-01-107-1971
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1919B05S04 Specifications

Fastener Length:	0.388 Inches Maximum
Head Style:	Modified Pan
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	755 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5056 Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.