

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1919B05S06       |
| Minimum Qty (MOQ):      | 20 EA               |
| NSN:                    | 5320-01-105-4522    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N NAS1919B05S06 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.513 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.067 Inches Minimum And 0.077 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.159 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.296 Inches Minimum And 0.328 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum  |
| <b>Special Features:</b>                              | Use With Single Action Installation Tools  |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Stem   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Locking Ring   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Locking Ring  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem  |
| <b>Surface Treatment:</b>                             | Anodize Stem Or Chromate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem |
| <b>Specification/standard Data:</b>                   | 80205-nas1919 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B05S06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.