

P/N NAS1919B06-03FC

Description

Fastener Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

 SKU / Model:
 NAS1919B0603FC

 Minimum Qty (MOQ):
 10 EA

 NSN:
 5320-01-423-2519

 Schedule B:
 7616.10.3000

 ECCN:
 9A991



^{*} See page 2 for technical characteristics

P/N NAS1919B06-03FC Specifications

Fastener Length:	0.350 Inches Nominal
Head Style:	Flat Chamfer
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Specification/standard Data:	80205-nas1919b06-03fc Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1919B06-03FC and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1919B06-03FC and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1919B06-03FC and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1919B06-03FC and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1919B06-03FC and selecting the property of the