

Description

Fastener Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B0603FC
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-423-2519
Schedule B:	7616.10.3000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS1919B06-03FC Specifications

Fastener Length:	0.350 Inches Nominal
Head Style:	Flat Chamfer
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Specification/standard Data:	80205-nas1919b06-03fc Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06-03FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.