

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B0607
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-231-2958
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1919B06-07 Specifications

Fastener Length:	0.600 Inches Maximum
Head Style:	Undercut Pan No. 2
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem
Specification/standard Data:	80205-nas1919 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.