

**Description**

Fastener Length: 13/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1919B06S04
Minimum Qty (MOQ):	10
NSN:	5320-01-092-5530
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1919B06S04 Specifications

<b>Fastener Length:</b>	0.412 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Nominal
<b>Shank Diameter:</b>	0.187 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.375 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Special Features:</b>	Requires Single Action,non-shifting,installation Tools
<b>Material:</b>	Aluminum Alloy 2024 Stem
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Anodize Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.