

Description

Fastener Length: 17/32",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B06S06
Minimum Qty (MOQ):	10
NSN:	5320-01-092-5531
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N NAS1919B06S06 Specifications

Fastener Length:	0.537 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	Requires Single Action,non-shifting,installation Tools
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Overall
Surface Treatment:	Anodize Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.