

Description

Fastener Length: 17/32",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1919B06S06 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-092-5531 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N NAS1919B06S06 Specifications

| | |
|---|--|
| Fastener Length: | 0.537 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Nominal |
| Shank Diameter: | 0.187 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.375 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Special Features: | Requires Single Action,non-shifting,installation Tools |
| Material: | Aluminum Alloy 2024 Stem |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec All Material Responses Overall |
| Surface Treatment: | Anodize Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.