

**Description**

Fastener Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1919B06S07       |
| Minimum Qty (MOQ):      | 5 EA                |
| NSN:                    | 5320-01-092-5532    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N NAS1919B06S07 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.600 Inches Nominal                                   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.080 Inches Nominal                                   |
| <b>Shank Diameter:</b>                                | 0.187 Inches Nominal                                   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                 |
| <b>Head Major Diameter:</b>                           | 0.375 Inches Nominal                                   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                   |
| <b>Grip Length:</b>                                   | 0.376 Inches Minimum And 0.437 Inches Maximum          |
| <b>Special Features:</b>                              | Requires Single Action,non-shifting,installation Tools |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Stem                               |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Locking Ring                       |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                             |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec All Material Responses Overall       |
| <b>Surface Treatment:</b>                             | Anodize Stem   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Stem     |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.