

Description

Fastener Length: 21/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B06S08
Minimum Qty (MOQ):	5
NSN:	5320-01-109-6084
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N NAS1919B06S08 Specifications

Fastener Length:	0.662 Inches Nominal
Head Style:	Undercut Pan No. 2
Head Height:	0.107 Inches Nominal
Shank Diameter:	0.250 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.500 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.469 Inches Nominal
Material:	Aluminum Alloy Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.