

Description

Fastener Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B06S09
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-343-9803
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1919B06S09 Specifications

Fastener Length:	0.725 Inches Maximum
Head Style:	Undercut Pan No. 2
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Special Features:	Use With Single Action Installation Tools
Material:	Aluminum Alloy 5056 Locking Ringaluminum Alloy 5056 Sleevealuminum Alloy 2024 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ringqq-a-430 Fed Spec Single Material Response Sleeveqq-a-430 Fed Spec Single Material Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.