

**Description**

Fastener Length: 23/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919B06S09
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-343-9803
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N NAS1919B06S09 Specifications

<b>Fastener Length:</b>	0.725 Inches Maximum
<b>Head Style:</b>	Undercut Pan No. 2
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Special Features:</b>	Use With Single Action Installation Tools
<b>Material:</b>	Aluminum Alloy 5056 Locking Ringaluminum Alloy 5056 Sleevealuminum Alloy 2024 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Locking Ringqq-a-430 Fed Spec Single Material Response Sleeveqq-a-430 Fed Spec Single Material Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.