

**Description**

Fastener Length: 23/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1919B06S09    |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5320-01-343-9803 |
| Schedule B:        | 7616.10.3000     |
| ECCN:              | EAR99            |



NO IMAGE  
AVAILABLE

## P/N NAS1919B06S09 Specifications

|  |   |
|--|---|
| <b>Fastener Length:</b>                      | 0.725 Inches Maximum  |
| <b>Head Style:</b>                           | Undercut Pan No. 2  |
| <b>Head Height:</b>                          | 0.080 Inches Minimum And 0.090 Inches Maximum   |
| <b>Shank Diameter:</b>                       | 0.186 Inches Minimum And 0.190 Inches Maximum   |
| <b>Shank Style:</b>                          | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                  | 0.356 Inches Minimum And 0.394 Inches Maximum   |
| <b>Expansion Device:</b>                     | Serrated Stem-type W  |
| <b>Grip Length:</b>                          | 0.501 Inches Minimum And 0.562 Inches Maximum   |
| <b>Special Features:</b>                     | Use With Single Action Installation Tools   |
| <b>Material:</b>                             | Aluminum Alloy 5056 Locking Ringaluminum Alloy 5056 Sleevealuminum Alloy 2024 Stem  |
| <b>Material Document And Classification:</b> | Qq-a-430 Fed Spec Single Material Response Locking Ringqq-a-430 Fed Spec Single Material Response Sleeveqq-a-430 Fed Spec Single Material Response Stem |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919B06S09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.