

## Description

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1919C0406
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-242-1848
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1919C04-06 Specifications

<b>Fastener Length:</b>	0.510 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Sleeve
<b>Surface Treatment:</b>	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty2 Cl 3 Fed Spec 2nd Treatment Response Sleeve Or Nas 4006 Assn Std 3rd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas1919 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919C04-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.