

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919C04S08
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-480-2563

NO IMAGE
AVAILABLE

P/N NAS1919C04S08 Specifications

Fastener Length:	0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.237 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	Helicopter,uh-tiger,fuselage
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Special Features:	Single Action,non-shifting Installation Tools,color Code Yellow On Spindle
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	11-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919C04S08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.