

**Description**

Fastener Length: 11/32", NAS1919 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1919C06S03U
Minimum Qty (MOQ):	10
NSN:	5320-01-613-7674
Schedule B:	7318.23.0000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1919C06S03U Specifications

<b>Fastener Length:</b>	0.350 Inches Minimum
<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.080 Inches Nominal
<b>Shank Diameter:</b>	0.187 Inches Nominal
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.375 Inches Nominal
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919C06S03U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.