

P/N NAS1919C06S04U

Description

NAS1919 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: NAS1919C06S04U

Minimum Qty (MOQ): 10

NSN: 5320-01-476-4790

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









P/N NAS1919C06S04U Specifications

Fastener Length:	0.412 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.190 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F16aircombfit; F-16 Aircraft
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Locking Ring Or Ams5690 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Or Qq-p-416, Ty Ii, Cl3 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1919C06S04U and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.