

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1919M0401
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-966-0362
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1919M04-01 Specifications

<b>Fastener Length:</b>	0.338 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.198 Inches Maximum
<b>Special Features:</b>	Sleeve May Be Cadmium Plated Per Qq-p-416,ty 2,cl 3 Or Aluminum Plated Per Nas 4006(optional); Lock Ring To Be Passivated Per Qq-p-35 If Material Is Iron Alloy
<b>Material:</b>	Iron Alloy 660 Locking Ring Or Nickel Locking Ringnickel Alloy Sleeveiron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Assn Std 2nd Material Response Locking Ringqq-n-281 Fed Spec Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.