

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919M0401
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-966-0362
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1919M04-01 Specifications

Fastener Length:	0.338 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Threaded Stem
Grip Length:	0.198 Inches Maximum
Special Features:	Sleeve May Be Cadmium Plated Per Qq-p-416,ty 2,cl 3 Or Aluminum Plated Per Nas 4006(optional); Lock Ring To Be Passivated Per Qq-p-35 If Material Is Iron Alloy
Material:	Iron Alloy 660 Locking Ring Or Nickel Locking Ringnickel Alloy Sleeveiron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Assn Std 2nd Material Response Locking Ringqq-n-281 Fed Spec Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.