

Description

Fastener Length: 11/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919M0401W
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-761-5995
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1919M04-01W Specifications

Fastener Length:	0.157 Inches Minimum And 0.177 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.032 Inches Minimum And 0.062 Inches Maximum
Minimum Tensile Strength:	675 Pounds Per Square Inch
Shear Strength:	1020 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall Or Steel Overall
Material Document And Classification:	Aisi 630 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04-01W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.