



Military-Fasteners.com

P/N NAS1919M04-01W

Description

Fastener Length: 11/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919M0401W
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-761-5995
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1919M04-01W Specifications

<b>Fastener Length:</b>	0.157 Inches Minimum And 0.177 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.032 Inches Minimum And 0.062 Inches Maximum
<b>Minimum Tensile Strength:</b>	675 Pounds Per Square Inch
<b>Shear Strength:</b>	1020 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Overall Or Steel Overall
<b>Material Document And Classification:</b>	Aisi 630 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1919 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04-01W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.