

Description

NAS1919 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1919M0402 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-360-9175 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1919M04-02 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.260 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.0540 Inches Minimum And 0.0640 Inches Maximum |
| Shank Diameter: | 0.1240 Inches Minimum And 0.1280 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.2380 Inches Minimum And 0.2520 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.0630 Inches Minimum And 0.1250 Inches Maximum |
| Material: | Iron Alloy 660 Locking Ring Or Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ringnickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeveiron Alloy 660 Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.