

Description

NAS1919M04S04U

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919M04S04U
Minimum Qty (MOQ):	20
NSN:	5320-01-508-8805
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1919M04S04U Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Rq-4a
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Special Features:	Single Action Installation Utilizes Drive Anvil Washer As Part Of Assy
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material Document And Classification:	Ams-5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring Or 99-281 Fed Spec 3rd Material Response Locking Ring
Material Document And Classification:	Ams-5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M04S04U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.