

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919M0505W
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-080-0606
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1919M05-05W Specifications

Fastener Length:	0.451 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	1565 Single Pounds Per Square Inch
Special Features:	Self-locking
Material:	Nickel Alloy 400 Body
Material:	Nickel Alloy 400 Sleeve
Material Document And Classification:	Qq-n-281 Form 7 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Form 7 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Specification/standard Data:	80205-nas1919 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M05-05W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.